

Telehandler / Zoom Boom

Used Telehandler Illinois - Telehandlers have numerous names including a teleporter, Cherry picker, telescopic handler or boom lift. This industrial machine is commonly used in a variety of industries and in agriculture. Similar to a crane and a forklift as it has a boom allowing it to extend forwards and upwards. Many different attachments can be used at the end of the articulating boom to facilitate a wide number of jobs. Popular attachments include a muck grab, bucket, winch or pallet forks. The pallet forks are the most popular telehandler attachment. These attachments help the operator transport different sized loads to many locations that would be considered unreachable with a traditional forklift. Telehandlers allow cargo pallets to be transported from trailers and placed on racking, rooftops or other difficult to reach locations. Often, high rooftop locations would need a crane although, telehandlers can accomplish these tasks much more efficiently. Of course, it isn't always affordable or practical to use secondary equipment or a crane to complete certain tasks. A bucket grab or a bucket is the most common attachments for telehandlers within the agricultural sector. Transporting items from unreachable places that cannot use a backhoe loader or a wheeled loader is one of the main advantages of using a telehandler. Telehandlers are beneficial for applications that would usually require a loading ramp or conveyor since they are capable of directly accessing trailers with high sides and hoppers. Relying on one piece of equipment to complete a variety of jobs saves time, money and storage. Telehandler machines can work in conjunction with a crane jib. Many attachments can be used such as power booms, grain and dirt buckets and rotators. Three-point linkage and power take-off can be used with agricultural models to make this machine particularly capable. Interestingly enough, the machines' main advantage is also its' biggest limitation. When raising or extending with heavy loads, the boom functions similar to a lever. Despite significant counterweights in the rear, the telehandler can be subject to instability at times, decreasing the lifting capacity as the working radius or distance between the center of the load and the front of the wheels increases. When a telehandler functions as a single boom loader (as opposed to twin arms) and carrying a heavy load, there can be a potential for weakness even in the best designs. A 5000 lb. capacity telehandler could lift 400 lbs. safely while fully extended with a retracted boom in conjunction with a low boom angle. This unit with a 5000 lb. lift capability and retracted boom could support as much as ten thousand pounds after the boom is raised seventy degrees. Monitoring the angle, weight and boom height, there are load charts on this equipment to outline which tasks can be safely conducted. Updated telehandler models have computers and sensors. When the telehandler limits have been surpassed, the operator is cut off and warned from supplying further control input. Front stabilizers that enhance the lifting capacity of the machine while stationary can make a huge difference. A mobile crane can also use a bucket is another option consisting of a stabilized rotary joint found between upper and lower frames. There are many models of telehandlers differing in size, weight, boom designs and reach. Telehandlers fall into the compact category if the unit weighs in at 11,000 lbs. or less. A two-stage boom is a popular option for compact models whereas the three or four boom design is common for bigger machines. The compact model showcases a low pivot boom to allow better cab visibility for the operator while transporting loads. Obviously, the compact telehandler has narrower and tinier dimensions. Compact telehandlers have a reach capacity ranging between 13 to 20 feet with a lift capacity ranging from 5k to 7k pounds. The versatility of the compact telehandler makes it popular in a variety of applications. Telehandlers can function as a pick and place unit or a tool carrier. This machine is often used in locations that are cramped and tight. It is common for contractors to use this machine during framing and for residential jobs where there are height restrictions. These machines can facilitate internal building access. Compact telehandlers are used in many applications including nurseries, erecting steel, multi-story construction, masonry, strip malls, garages and similar jobs. Telehandlers are employed by agri-business and farming applications to complete many jobs. Telehandlers come with crab steering or two or four-wheel drive

options. The unit can travel over longer ranges at higher speeds with two-wheel drive, making it ideal for moving throughout job sites. Four-wheel drive units can travel over harder terrain while offering a tighter turning radius. Crab steering increases overall maneuvering and enables the front and back wheels to move 45 degrees to the left or the right. Compact telehandlers have varying cab environments. There is a rollover protective cage to enhance safety on less expensive models. Newer units come with windshield wipers, a defroster, a heater and a totally enclosed cab. Operators enjoy spacious accommodation for ultimate comfort. Additional options including satellite radio, air conditioning, armrests, cup holders, suspension seats and tilt steering are available. Many high-pressure hydraulics and high-flow auxiliary hydraulics operate the numerous attachments. These attachments increase the functions the machine is capable of. Ground engaging work is often completed by compact units. It is simple to transform a compact telehandler into a mini excavator with a bucket attachment. Light-duty to heavy-duty buckets can be attached for transferring material, side-shifting and rotating fork carriages are relied on for pick and place situations, augers for drilling post holes or planting trees or pier supports, truss booms for extending reach, crane hooks, brooms for sweeping and more. Skid steer attachments are being made for versatility and other compact telehandler designs.